



<b>PUMP BOWL PERFORMANCE CURVE</b>	
<b>TYPE: MIXED FLOW</b>	<b>IMPELLER DIA: 21.1"</b>
<b>MODEL NO: MF 24-661400SB+</b>	<b>SPEED: As Noted</b>
<b>INTAKE DIA: 32"</b>	<b>DISCHARGE COLUMN DIA: 24"</b>
<b>CURVE NO.: N2466B</b>	<b>Ns: 6600      Code B</b>
<b>SINGLE STAGE PERFORMANCE</b> FOR TWO STAGES MULTIPLY HEAD AND HORSEPOWER BY 2.0 AND EFFICIENCY BY 1.0 PERFORMANCE IS BASED ON PUMPING CLEAR, NONAERATED WATER, WITH A SPECIFIC GRAVITY OF 1.0, TEMPERATURE 85 °F OR LESS AND AT SEA LEVEL. PUMP PERFORMANCE MAY BE AFFECTED BY HIGHER TEMPERATURES, SPECIFIC GRAVITY, ALTITUDES AND SUMP CONDITIONS	

IT IS HEREBY CERTIFIED THAT THIS CURVE REPRESENTS THE TRUE PERFORMANCE CHARACTERISTICS OF THE MWI PUMP MODEL SHOWN AND WAS OBTAINED BY SCALE MODEL TEST AND CALCULATIONS IN ACCORDANCE WITH STANDARDS OF THE HYDRAULIC INSTITUTE.

MWI CORPORATION  
CERTIFIED BY

MWI CORPORATION  
Deerfield Beach, Florida